DH-SD59225U-HNI

2MP 25x Starlight IR PTZ Network Camera



- 1/2.8” 2Megapixel Exmor R CMOS
- Powerful 25x optical zoom
- Starlight technology
- H.265 Encoding
- Max. 50/60fps@1080P, 25/30/50/60fps@720P
- Auto-tracking and IVS(Optional)
- Support PoE+
- IR distance up to 150m
- IP66 ingress protection



System Overview

Featuring with powerful optical zoom and accurate pan/tilt/zoom performance, the SD59 series PTZ camera can provide large monitoring range and great detail. The camera delivers 1080P resolution at 50/60 fps, with 25x optical zoom, and has very excellent low light performance due to adopting the latest starlight technology. SD59 series PTZ is equipped with quick and smooth control, high quality image and good protection, which make it can meet most of the requirements of video surveillance applications.

Functions

Starlight Technology
Thanks to our experience and expertise in hardware and software development , the camera is equipped with the latest image processing algorithm, high performance hardware and high quality optical components, which make the camera have very exellent low light performance. In most conditions, this camera can deliver clear, bright and low-noise color images.

Wide Dynamic Range
Embedded with industry leading wide dynamic range (WDR) technology, vivid pictures are achieved even in the most intense contrast lighting conditions. For applications with both bright and low lighting conditions that change quickly, true WDR (120dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

Auto-tracking
The camera supports auto-tracking. The tracking action can be triggered manually or automatically by defined rules. Once rules are triggered, the camera can zoom in and track the defined target automatically.

H.265
The camera supports H.265 encoding, which provides a savings of more than 50% of bandwidth and storage compared with H.264. This technology can help our customers to reduce the cost of the project and improve the transmission efficiency.

Environmental
With a temperature range of -40 °C to +70 °C (-40 °F to +158 °F), the camera is designed for extreme temperature environments. Subjected and certified to rigorous dust and water immersion tests, the IP66 rating makes it suitable for demanding outdoor applications.
Protection
This camera suits even the harsh conditions for outdoor applications. Its 6KV lightning rating provides protection against the camera and its structure from the effects of lightning.

Interoperability
The camera conforms to the ONVIF (Open Network Video Interface Forum) and PSIA (Physical Security Interoperability Alliance) specifications, ensuring interoperability between network video products regardless of manufacturer.

Technical Specification

Camera		
Image Sensor		1/2.8" Exmor R CMOS
Effective Pixels		1920(H) x 1080(V), 2 Megapixels
RAM/ROM		1024M/128M
Scanning System		Progressive
Minimum Illumination		Color: 0.005Lux@F1.6; 0Lux@F1.6 (IR on)
S/N Ratio		More than 55dB
IR Distance		Distance up to 150m (492ft)
IR On/Off Control		Auto/Manual
IR LEDs		4
Lens		
Focal Length		4.8mm~120mm
Max. Aperture		F1.6 ~ F4.4
Angle of View		H: 59.2° ~ 2.4°
Optical Zoom		25x
Focus Control		Auto/Manual
Close Focus Distance		100mm~ 1000mm
PTZ		
Pan/Tilt Range		Pan: 0° ~ 360° endless; Tilt: -15° ~ 90°,auto flip 180°
Manual Control Speed		Pan: 0.1° ~300° /s; Tilt: 0.1° ~200° /s
Preset Speed		Pan: 400° /s; Tilt: 300° /s
Presets		300
PTZ Mode		5 Pattern, 8 Tour, Auto Pan ,Auto Scan
Speed Setup		Human-oriented focal Length/ speed adaptation
Power up Action		Auto restore to previous PTZ and lens status after power failure
Idle Motion		Activate Preset/ Scan/ Tour/ Pattern if there is no command in the specified period
Protocol		DH-SD
Intelligence		
Auto Tracking		Support
IVS (optional)		Tripwire, Intrusion,Abandoned/Missing, Face Detection
Video		
Compression		H.265/H.264 / MJPEG
Streaming Capability		3 Streams
Resolution		1080P(1920×1080)/720P(1280×720)/ D1(704×576/704×480)/CIF(352×288/352×240)
Frame Rate	Main stream	1080P/720P/D1(1~50/60fps),
	Sub stream1	D1/CIF(1 ~ 25/30fps)
	Sub stream2	1080P/720P/D1/ CIF (1 ~ 25/30fps)

Bit Rate Control	CBR/VBR
Bit Rate	H.265/H.264: 448K ~ 8192Kbps, MJPEG: 5120K ~ 10240Kbps
Day/Night	Auto(ICR) / Color / B/W
Backlight Compensation	BLC / HLC / WDR (120dB)
White Balance	Auto,ATW,Indoor,Outdoor,Manual
Gain Control	Auto / Manual
Noise Reduction	Ultra DNR (2D/3D)
Motion Detetion	Support
Region of Interest	Support
Electronic Image Stabilization (EIS)	N/A
Defog	Support
Digital Zoom	16x
Flip	180°
Privacy Masking	Up to 24 areas
Audio	
Compression	G.711a/G.711u(32kbps)/PCM(128kbps)
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6,HTTP,HTTPS,SSL,TCP/IP, UDP,UPnP, ICMP,IGMP,SNMP,RTSP,RTP, SMTP, NTP,DHCP, DNS,PPPOE,DDNS,FTP, IP Filter,QoS,Bonjour,802.1x
Interoperability	ONVIF, PSIA, CGI
Streaming Method	Unicast / Multicast
Max. User Access	20 users
Edge Storage	NAS (Network Attached Storage),Local PC for instant recording, 128GB
Web Viewer	IE10/Google/Firefox/Safari...
Management Software	Smart PSS, DSS
Smart Phone	iPhone, iPad, Android, Windows Phone
Certifications	
Certifications	CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB,ANSI C63.4- 2014 UL: UL60950-1+CAN/CSA C22.2,No.60950-1
Interface	
Video Interface	N/A
Audio Interface	1/1
RS485	N/A
Alarm	2/1
Electrical	
Power Supply	AC24V/3A(±10%), PoE+(802.3at)
Power Consumption	13W,23W (IR on)

Environmental	
Operating Conditions	-40ºC ~ 70ºC (-40°F ~ +158°F) / Less than 90% RH
Ingress Protection	IP66
Vandal Resistance	N/A
Construction	
Casing	Metal
Dimensions	Φ186.0(mm) x 309(mm)
Net Weight	3.5kg(7.72lb)
Gross Weight	6.8kg(14.99lb)

Ordering Information

Type	Part Number	Description
2MP PTZ Camera	DH-SD59225U-HNI	2MP 25x Starlight IR PTZ Network Camera, WDR, PAL
	DH-SD59225UN-HNI	2MP 25x Starlight IR PTZ Network Camera, WDR, NTSC
	SD59225U-HNI	2MP 25x Starlight IR PTZ Network Camera, WDR, PAL
	SD59225UN-HNI	2MP 25x Starlight IR PTZ Network Camera, WDR, NTSC
Accessories	PFB300S	Wall Mount
	PFA110	Mount Adapter
	AC24V/3A	Power Supply
	PFA140	Power box
	PFB300C	Ceiling Mount
	PFA120	Water-proof Junction Box
	PFA150	Pole Mount
	PFA151	Corner Mount
	PFB303S	Parapet mount

Accessories

Included:



PFB300S
Wall Mount



PFA110
Mount Adapter



AC24V/3A
Power Supply

Optional:



PFA140
Power box



PFB300C
Ceiling Mount



PFA120
Junction Box









PFA150
Pole Mount



PFA151
Corner Mount




PFB303S
Parapet Mount

Ceiling Mount	Junction Mount
PFA110 + PFB300C	PFA110 + PFB300S + PFA120
	
Power Box Mount	**Pole Mount**
PFA110 + PFB300S + PFA140	PFA110 + PFB300S + PFA150
	
Corner Mount	**Parapet Mount**
PFA110 + PFB300S + PFA151	PFA110 + PFB303S
	

Rev 001.001 © 2016 Dahua". All rights reserved.

Dimensions (mm)



© 2016 Dahua". All rights reserved.